

FRESH PR 40 C (COD. EBM010422)



Upright display cooler

Technical data

| | |
|-------------------------|--|
| Temperature | +3°C +10°C |
| Voltage and Frequency | 230 Volt 50 Hz |
| Gas | R134a |
| Net dimension | 600 x 620 x 2045 mm (w x d x h) |
| Packed dimension | 655 x 690 x 2110 mm (w x d x h) |
| Gross capacity | 380 dm ³ |
| Net capacity | 310 dm ³ |
| Gross weight | 94 Kg |
| Net weight | 91 Kg |
| Heat insulation | In polyurethane injected "HCFC/CFC" free |
| External cabinet | White painted sheet |
| Cabinet back | Galvanized steel sheet |
| Inner tank | White thermoformed plastic |
| Door frame - colour | White prepainted aluminium |
| Glass | 29 mm insulating glasses |
| Handle | White plastic (built in the door frame) |
| Handle insert | - - - |
| Light box - colour | White plastic |
| Light box opaline | Back lighted white opale plastic |
| Control board cover | White plastic |
| Frontal grid - colour | White painted sheet |
| Compressor | 1/5 hp |
| Power consumption | 280 Watt |
| Condensator | Static condensation system (fan assisted) |
| Evaporator | Roll bond (fan assisted) |
| Climatic class - EN 441 | 4 (30°C 55% R.H.) |
| Plug | European - Angular Plug |
| Thermometer | Mechanic |
| Thermostat | Mechanic |
| Inner shelves | White plastified shelves - 5 removable + 1 in the bottom of the tank |
| Standard equipment | Internal light |
| Optional | Lock - Wheels - Legs |
| Producer brand | FRAMEC |

The manufacturer will reserve the right to make any modification without prior notice.

| | | | |
|---------|------------|------------|-------------|
| Version | Updated on | Written by | Approved by |
| 1 | 18/10/2007 | D. Capuano | R. Bovo |